

TERRAMAC[®] RT9 RUBBER TRACK CARRIER

Standard RT9 Specs

The Terramac[®] RT9 features an 18,000 lb. carrying capacity and is the only carrier in its class with a non-permitted load for ease of transport. Available with a rock bed, convertible dump-to-flat bed or flat bed this versatile unit travels effortlessly across any type of terrain.



DIMENSIONS	
Full Length	18' 10"
Full Width	8' 5"
Wheel Base	12' 9"
Min Ground Clearance	20"
Front Overhang	2' 6"
Track Width	27"
Track Length	32' 2"
Full Height	9' 11"
Height of Rock Bed	5' 10"
Height of Rock Bed Side (Vessel)	21"
Length of Rock Bed (Vessel)	10' 5"
Width of Rock Bed (Vessel)	7' 3"
Dumping Angle	60°
Machine Weight (no bed)	21,500 lbs.
Machine Weight (with bed)	26,000 lbs.

HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	43 gpm / side
Relief Valve Piston Pump	5,600 PSI
Tandem Gear Pump Capacity	
Front Section (HST Drive)	20 gpm @ 500 PSI
Rear Section (Aux Output)	25 gpm @ 2500 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7
Displacement	409 cu. in.
Horsepower	230 HP
Electrical System	12 VDC
Battery	8D with 1400 CCA
Fuel Capacity	42 gallons

PERFORMANCE	
Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	2.5 mph
Travel Speed - 2nd Gear	6 mph
Gradability (unloaded)	32%
Turning Radius	10 ft
Ground Pressure (full capacity)	5.1 PSI
Ground Pressure (unloaded)	3.0 PSI

TERRAMAC[®] RT9 RUBBER TRACK CARRIER

Standard RT9 Units & Dimensions

