

# TERRAMAC® RT6 RUBBER TRACK CARRIER

## Standard RT6 Specs

The Terramac® RT6 features a 12,000 lb. carrying capacity and is built to be nimble while providing the power needed to accomplish the task at hand. This unit can accommodate a wide variety of support equipment making it ideal for an array of projects including pipeline, environmental, utility, general construction and many more.



DIMENSIONS	
Full Length	16' 2"
Full Height	9' 6"
Width Over Tracks	8' 2"
Min. Ground Clearance	18"
Front Overhang	3' 7"
Track Gauge (Center-to-Center)	6' 2"
Track Width	23.6"
Undercarriage Length (Idler to Drive Hub)	12' 1"
Dump Bed Loading Height Over Side	4' 11"
Height of Dump Bed Side (Vessel)	15"
Length of Dump Bed (Vessel)	9' 2"
Width of Dump Bed (Vessel)	7' 7"
Dumping Angle	60°
Machine Weight (with bed)	17,990 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 4.5
Displacement	272 cu. in.
Horsepower	130 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA
Fuel Capacity	40 gallons

HYDRAULICS	
Transmission	HST
Drive Pump Max Flow (x2)	32 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (Aux Output)	14 gpm @ 3000 PSI
Rear Section (HST Drive)	20 gpm @ 350 PSI

PERFORMANCE	
Max. Carrying Capacity	12,000 lbs.
Travel Speed - 1st Gear	3.9 mph
Travel Speed - 2nd Gear	6.7 mph
Gradability	45% (24°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	5.3 PSI
Ground Pressure (unloaded)	3.2 PSI

# TERRAMAC<sup>®</sup> RT6 RUBBER TRACK CARRIER

## Standard RT6 Units & Dimensions

