

TERRAMAC[®] RT9 STRAW BLOWER



All Terrain Mulching System

The Terramac[®] RT9 with Straw Blower is designed with your mulching needs in mind; the powerful Reinco TM-35 power mulcher has a bale capacity for up to 5 tons of hay or straw per hour with a 60 foot direct discharge. Safety is top of mind with the rails on the RT9.

The RT9 is a rubber tracked all terrain utility vehicle that is easily maneuvered over rough, soft and steep ground conditions. Wherever your job site may be, the RT9 will lead the way and work hard all day.

STRAW BLOWER FEATURES

- 33.5 HP EC diesel engine package
- 5 ton per hour mulch output
- Discharge 60 feet in still air
- Discharge and suction hose options
- Granular broadcast option





TERRAMAC® RT9 STRAW BLOWER

Standard RT9 Specs*

PERFORMANCE

Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	2.5 mph
Travel Speed - 2nd Gear	5.4 mph
Gradeability	58% (32°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	6.4 PSI
Ground Pressure (unloaded)	3.8 PSI

HYDRAULICS

Transmission	HST
Drive Pump Max Flow (x2)	43 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (AUX Output)	25 gpm @ 3000 PSI
Rear Section (HST Drive)	22 gpm @ 550 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

ENGINE

Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	225 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA ea.
Fuel Capacity	64 gallons

DIMENSIONS

Full Length	19' 6"
Full Height	9' 11"
Width Over Tracks	8' 3"
Min Ground Clearance	21"
Front Overhang	2' 6"
Track Gauge (Center-to-Center)	6'
Track Width	27.5"
Undercarriage Length	
(Idle to Drive Hub)	12' 3"
Machine Weight (no bed)	21,500 lbs.
Machine Weight (with bed)	26,000 lbs.

* Based on standard machine. Specifications will vary based on optional equipment selected.

Straw Blower Specs

SIZE:

Length 79" (2.1 m), Width 44" (1.12 m), Height 64-1/2" (1.7 m).

WEIGHT:

Standard unit weight is 1200 pounds (544 kg). Uncrated volume is 150cu. feet (4.24 cu. m).

ENGINE:

Standard 33.5 HP Water Cooled EC Kubota Diesel.

DRIVE:

Direct flexible insert drive coupling features easy access replacement insert(s).

FLAIL:

Three fully adjustable full hardened chain flail stations. Optional flail knives make easy work of tough materials.

BLOWER:

22-5/8" OD six blade reinforced material handling type wheel, dynamically and statically balanced.

DISCHARGE:

UMHW nylon bearing mounted, counter balanced, 360° horizontal rotation, 60° vertical articulation, urethane abrasion resistant rolling boom seals and stainless steel side wipers.

FEED TRAY:

Single section extends 50" from drum entrance. Tray elevation from truck bed is 41".

OPTIONAL EQUIPMENT

HOSE PLACEMENT:

Remote discharge kit includes 25 ft. of 8" helically wound, flexible urethane cuffed hose, boom discharge adapter and hand held discharge playpipe. Connect additional 25 ft. hose sections to accommodate hard to reach areas.

SUCTION KIT:

Adapter kit converts beater drum to suction chamber for leaf, mulch and light debris pick-up. Attach up to 50 ft. of 8" hose. The discharge playpipe is designed to double as a pick-up nozzle.

SEED DISTRIBUTOR:

2.0 bu. broadcast type distributor provides uniform placement of dry granular materials for simultaneous seeding and fertilizing.

FORKLIFT FRAME:

Sturdy formed steel and electrically welded frame provides for moving the machine around sites where accessibility is limited. Provides easy pickup from end or side of machine.