



Rubber Track Carriers

Terramac RT9

Unit Specifications and Dimensions

DIMENSIONS	
Full Length	17' 7"
Full Width	8' 5"
Wheel Base	12' 9"
Min Ground Clearance	20"
Front Overhang	2' 6"
Track Width	27"
Track Length	32' 2"
Full Height	9' 3"
Height of Dump Bed	4' 4"
Height of Dump Side	16"
Length of Dump Bed	12'
Width of Dump Bed	8' 6"
Dumping Angle	60°
Machine Weight (no bed)	15,000 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7
Displacement	409 cu. in.
Horsepower	230 HP
Electrical System	12 VDC
Battery	8D with 1500 CCA
Fuel Capacity	42 gallons



HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	43 gpm / side
Relief Valve Piston Pump	5,600 PSI
Tandem Gear Pump Capacity	
Front Section (HST Drive)	20 gpm @ 500 PSI
Rear Section (Aux Output)	25 gpm @ 2500 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

PERFORMANCE	
Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	4.7 mph
Travel Speed - 2nd Gear	7 mph
Gradability (unloaded)	32%
Turning Radius	10 ft
Ground Pressure (full capacity)	4.9 PSI

BROUGHT TO YOU BY:



630-365-1649 | info@rigsourceinc.com
www.rigsourceinc.com | www.terramac.com



Rubber Track Carriers

Terramac RT9

Unit Specifications and Dimensions

DIMENSIONS	
Full Length	5.4 m
Full Width	2.6 m
Wheel Base	3.9 m
Min Ground Clearance	.51 m
Front Overhang	.46 m
Track Width	.68 m
Track Length	9.8 m
Full Height	2.8 m
Height of Dump Bed	1.2 m
Height of Dump Side	.4 m
Length of Dump Bed	3.7 m
Width of Dump Bed	2.5 m
Dumping Angle	60°
Machine Weight (no bed)	6,803 kg

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7
Displacement	6.7 l
Horsepower	172 kW
Electrical System	12 VDC
Battery	8D with 1500 CCA
Fuel Capacity	160 l



HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	195 L/m
Relief Valve Piston Pump	386 bar
Tandem Gear Pump Capacity	
Front Section (HST Drive)	75 L/m @ 34 bar
Rear Section (Aux Output)	95 L/m @ 172 bar
Optional Pump Drive	95 L/m @ 172 bar

PERFORMANCE	
Max. Carrying Capacity	8,165 kg
Travel Speed - 1st Gear	736 km/h
Travel Speed - 2nd Gear	25.5 km/h
Gradability (unloaded)	32%
Turning Radius	3 m
Ground Pressure (full capacity)	.34 kg/c ²

BROUGHT TO YOU BY:



630-365-1649 | info@rigsourceinc.com
www.rigsourceinc.com | www.terramac.com